

Grazer

Wall Washer Luminaire



The Wall Grazer fixture delivers high power performance lighting for interior & exterior wall washing applications. The Wall Grazer add linear washing brilliant led performance to new installation are can drastically enhance an existing structure as a fluorescent replacement wall wash, retrofit system . Linea is beast value for money .

Wall Grazer designed for seamless continuous mounting .Optimal performance can be achieved for various mounting heights.

A maintenance free fixture with long life span and low cost & easy installation .

La luminaria Wall Grazer ofrece una iluminación de alto rendimiento para aplicaciones de lavado de paredes interiores y exteriores. El Wall Grazer agrega el funcionamiento llevado brillante brillante del lavado a la nueva instalación puede realzar drástico una estructura existente como lavado de la pared del reemplazo fluorescente, sistema del retrofit. Wall Grazer es valor de la bestia para el dinero.

Wall Grazer diseñado para un montaje continuo sin costura. Se puede lograr un rendimiento óptimo para diversas alturas de montaje.

Un accesorio sin mantenimiento con larga vida útil y bajo costo & Fácil instalación .

outdoor

Grazer

Linear Wall Washers



Wall Grazer

Product Information

- > Lamp Type
LED
- > Dimming Options
Dali, Triac
- > Nominal Operating Voltage
DC:24V/AC:180-240VAC / 50Hz
- > Control Type
Switch, Dmx 512
- > Median useful life
L70B10 50,000 Hours
- > Materials
Die-Cast Alum + Tempered Glass, Stainless Steel Screws
- > Installation Type
Surface Mounted
- > Ingress protection
Code IP66
- > Mech. impact
Ik08
- > Power Factor
0.9+
- > Working Temperature
Ta : -15°C ~ +55°C
- > Protection Class
IEC Safety Class I
- > Finish
Polyester powder coat with phospho-chromated pre finish.



A Symmetrical

Model model	Power energia	Color temperature CCT temperatura del color	Luminous lm luminoso	Flux flujo	Beam angle deg. Ángulo de haz
IL Grazer	18 24 36	3000K, 4000K, 5700K, RGB	1566 1676 2040 4320 6485		8°x 10°, 8°x 15°, 8 x 30°, 18° + 55°, 15°, 30°

outdoor

Grazer



Linear Wall Washers

Ordering Guide Sample Ejemplo de la guía de pedido

MO-WATT-ITL-CT-VA-OA-OB												
EXAMPLE : Grazer 18 SM 30 BA01 OA02												
MO	Model	Wattage	ITL	Installation Type	CT	C.C.T	BA+	Beam Type B	OA+	Control Mode	OB+	Voltage
	Grazer	18	SM	Surface Mounted	27	2700K	01	18°x55°	01	Switch	01	220VAC
	S	24			30	3000K	02	18°x55°	02	DMX 512	02	24VDC
	Grazer	36			40	4000K	03	18°x55°				
	M				57	5700K						
	Grazer				80	RGB						

*All power are subjected to module connected wattages , for luminaire wattages please refer datasheet .

Product Dimensions Dimensión del producto



Model / Watt modelo / power	Diameter A diámetro	Height B altura	Width C fondo
18	1000m	82mm	30mm
24	m	82mm	30mm
36	1000m	82mm	30mm
	m		
	1000m		
	m		

Planning Aid

** For Planning Aid , visit <https://www.ivorylighting.com/appointment>

View Online

Linea, Category page: visit <https://www.ivorylighting.com/outdoor/architecture>

5 Years Warranty

As a Market leading outdoor luminaire, expert IVORY Lighting provides a five-year warranty for its complete product range.

IVORY Lighting is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. The right is reserved to change specifications without prior notification or public announcement. All goods supplied by the company are supplied subject to the company's General Conditions of Sale, a copy of which is available on request. All measurements are in millimetres and weights in kilograms unless otherwise stated.

